

## Vertical Band Saws

### Standard Features

- 230/460/60/3 Electricals
- Magnetic Starter with 110V Control Circuit and Overload Protection
- Three (3) Hp TEFC Motor
- Dual Range Transmission
- 1/2" and 3/4" Chevron type Blade Guides with Back-Up Roller
- 26-3/4" x 29" Heavy Duty Cast Iron Table with two-way tilt ( 5°L & 45°R)
- 26-3/4" x 29" Heavy Duty Cast Iron Table with two-way tilt (15°L & 45°R) Four (4) T-Slots on Top (Hydraulic table only) Table Travel 13"
- Bonded Rubber Band Wheels
- 110V Work Light
- Built-in Air Chip Blower
- Blade Tension Indicator
- Blade Speed Indicator
- 3/4" Carbon Hardback Blade
- Locking Band Wheel Doors
- Operation and Parts Manual
- Two (2) Year Limited Warranty



### Optional Equipment

- 1" Capacity Blade Welder, Shear and Flash Grinder
- Rip Fence
- Miter Gauge
- 1/8", 1/4", 3/8", 1/2", 5/8", 3/4" and 1" Chevron Guide Inserts

Specifications	V2012F	V2012H	V2812F	V2812H
Throat	20"	20"	28"	28"
Work Height	12 <sup>3</sup> / <sub>4</sub> "	12 <sup>3</sup> / <sub>4</sub> "	12"	12"
Drive Motor (Hp)	3	3	3	3
Blade Length	159"-162"	159"-162"	197"-199"	197"-199"
Blade Width	1/8"-1"	1/8"-1"	1/8"-1"	1/8"-1"
Blade Speed (fpm)	50-5200	50-5200	50-5200	50-5200
Dimensions				
Length	51"	51"	61"	61"
Width	41"	44"	41"	44"
Height	81"	81"	91"	91"
Net Weight (lbs)	1,390	1,500	1,650	1,760
Shipping Weight (lbs)	1,540	1,650	1,800	1,900

## Simply the Best

Distributed By:

